


PROFESSIONAL
CITY LAMP

AR111



Ø 111 x 57 mm - 165 g

		OUTPUT 360°	OUTPUT 90°			
Connection with terminal	15 W = 100 W	1.200 lm	1.100 lm	3000 K	CL-152430	19,00 €
				4000 K	CL-152440	



220-240 V IP20 24°

INCLUDED



DRIVER ESTERNO EXTERNAL DRIVER



Ø 111 x 68 mm - 118 g

		OUTPUT 360°	OUTPUT 90°			
GU10	15 W = 100 W	1.200 lm	1.100 lm	3000 K	CLGU10-153830	15,00 €
				4000 K	CLGU10-153840	



GU10 220-240 V IP20 38°


PROFESSIONAL
SUPERLED

AR111 - G53



Ø 111 x 65 mm - 130 g

		OUTPUT 360°	OUTPUT 90°			
G53	12 W	1.020 lm	900 lm	3000 K	SLAR111-124030	15,50 €
				4000 K	SLAR111-124040	



G53 12 V AC/DC IP20 38°

TECHNICAL NOTES

ALIMENTAZIONE CON TRASFORMATORI ELETTROMAGNETICI
POWER SUPPLY WITH ELECTROMAGNETIC TRANSFORMERS

PROFESSIONAL
SERIE LIGHT

E27



8 W - Ø 63 x 89 mm - 54 g
10 W - Ø 95 x 105 mm - 96 g
15 W - Ø 121 x 140 mm - 125 g

PAR 38°		OUTPUT 360°	OUTPUT 90°			
E27	8 W	640 lm	640 lm	3000 K	PAR20-082730	6,50 €
				4000 K	PAR20-082740	
	10 W	870 lm	730 lm	3000 K	PAR30-102730	11,00 €
				4000 K	PAR30-102740	
	15 W	1.270 lm	1.100 lm	3000 K	PAR38-152730	13,00 €
				4000 K	PAR38-152740	



E27 220-240 V IP20 38°

TECHNICAL NOTES

SPECIALELENTE PER OMOGENEITÀ DEL FASCIO LUMINOSO
SPECIAL LENS FOR UNIFORMITY LIGHT BEAM